

GoldTop Air Vent

FV180, FV180A, FV183

PRODUCT DATA



FEATURES

- Male Connection.
- Four Sizes Available.
- Higher Capacity.
- Vents Up To 150 psi (1034 kPa).

SPECIFICATIONS

Maximum Pressure: 150 psi (1034 kPa).

Maximum Temperature: 240 °F (116 °C).

Product Number	Height	Diameter	Connection in inches	Weight in lb (kg)
	in inches (mm)			
FV180	3.25 (83)	1.85 (47)	1/8 NPT	0.4 (0.2)
FV180A	3.25 (83)	1.85 (47)	1/4 NPT	0.4 (0.2)
FV183	3.82 (97)	1.85 (47)	3/4 NPT	0.6 (0.3)

APPLICATION

The GoldTop Air Vent is a spring-loaded, float type air vent. It is used in heating systems to vent air, which has accumulated due to the heating of cold water.

INSTALLATION

Install GoldTop into the heating system at the high point, or wherever air would accumulate to remove the air. Typical recommended locations are: on boiler top, on top of an air purger, etc. Loosen thumb cap to allow air to vent.

ORDERING INFORMATION

When purchasing replacement and modernization products from your TRADELINE® wholesaler or distributor, refer to the TRADELINE® Catalog or price sheets for complete ordering number.

If you have additional questions, need further information, or would like to comment on our products or services, please write or phone:

1. Your local Honeywell Automation and Control Products Sales Office (check white pages of your phone directory).
2. Honeywell Customer Care
1885 Douglas Drive North
Minneapolis, Minnesota 55422-4386

In Canada—Honeywell Limited/Honeywell Limitée, 35 Dynamic Drive, Toronto, Ontario M1V 4Z9.

International Sales and Service Offices in all principal cities of the world. Manufacturing in Australia, Canada, Finland, France, Germany, Japan, Mexico, Netherlands, Spain, Taiwan, United Kingdom, U.S.A.

Automation and Control Solutions

Honeywell International Inc.
1985 Douglas Drive North
Golden Valley, MN 55422
customer.honeywell.com

Honeywell Limited-Honeywell Limitée
35 Dynamic Drive
Toronto, Ontario M1V 4Z9

© U.S. Registered Trademark
© 2007 Honeywell International Inc.
62-3086 J.I. 04-07



Printed in U.S.A. on recycled paper containing at least 10% post-consumer paper fibers.

